



NATIONAL ENERGY TECHNOLOGY LABORATORY



Cost and Performance Metrics Used to Assess Carbon Utilization and Storage Technologies

February 11, 2014

DOE/NETL-341/093013



OFFICE OF FOSSIL ENERGY

Disclaimer

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference therein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed therein do not necessarily state or reflect those of the United States Government or any agency thereof.

**Cost and Performance Metrics
Used to Assess Carbon Utilization
and Storage Technologies:**

DOE/NETL-341/093013

Final Report

February 11, 2014

NETL Contact:

James Black

General Engineer

Office of Program Planning and Analysis

National Energy Technology Laboratory

www.netl.doe.gov

Prepared by:

Energy Sector Planning and Analysis (ESPA)

**Peter Kabatek
WorleyParsons Group, Inc.**

**Alexander Zoelle
Booz Allen Hamilton, Inc.**

DOE Contract Number DE-FE0004001

Acknowledgments

This report was prepared by Energy Sector Planning and Analysis (ESPA) for the United States Department of Energy (DOE), National Energy Technology Laboratory (NETL). This work was completed under DOE NETL Contract Number DE-FE0004001. This work was performed under ESPA Task 04001.341.03, Activity 016.

The authors wish to acknowledge the excellent guidance, contributions, and cooperation of the NETL staff, particularly:

James Black, General Engineer

This page intentionally left blank.

Table of Contents

1 Background	1
2 Introduction	1
3 Developing the Metrics	2
4 Methodology	3
4.1 Performance Metrics	4
4.1.1 CO ₂ Utilization Efficiency	4
4.1.2 CO ₂ Utilization Potential	4
4.1.3 CO ₂ Utilization Intensity	4
4.1.4 CO ₂ Integration Reaction Rate	5
4.1.5 CO ₂ Energy Utilization.....	5
4.2 Cost Metrics	5
4.2.1 Product Marketability	5
4.2.2 Incremental Cost Reduction.....	5
4.2.3 Cost per Tonne CO ₂ Utilized.....	6
4.3 Emissions Metrics	6
4.3.1 CO ₂ Emissions Reduction	6
4.3.2 CO ₂ Avoided Potential	6
4.4 Market Metric	7
4.4.1 Product Supply-Demand.....	7
4.5 Safety Metric.....	7
4.5.1 Relative Safety and Environmental Benefits	7
5 Conclusions.....	8
6 References.....	9

Acronyms and Abbreviations

CCUS	Carbon capture, utilization, and storage	NETL	National Energy Technology Laboratory
CO ₂	Carbon dioxide	NFPA	National Fire Protection Association
DOE	Department of Energy	R&D	Research and development
ESPA	Energy Sector Planning and Analysis	t	tonne (1,000 kg)
h, hr	Hour	U.S.	United States

1 Background

In an effort to reduce carbon dioxide (CO₂) emissions from various industrial and power generation processes to the atmosphere, the United States (U.S.) Department of Energy (DOE) National Energy Technology Laboratory (NETL) is funding research intended to advance state-of-the-art technologies that address the use of CO₂ in a variety of processes. Much of this research is funded and managed in the CO₂ Utilization Focus Area of the Carbon Storage Program. [1]

CO₂ utilization efforts focus on pathways and novel approaches for reducing CO₂ emissions by developing beneficial uses for CO₂ that will mitigate greenhouse gas emissions. Utilization is an important component in carbon sequestration, also called storage. Some of the applicable approaches are conversion of CO₂ into useful chemicals and polycarbonate plastics, storage of CO₂ in solid materials having economic value, indirect storage of CO₂, and other breakthrough concepts. The term sequestration for this report is defined as the segregation of CO₂, either chemically, as in chemical utilization, or physically, as in geologic storage. This concept is therefore named carbon capture, utilization, and storage (CCUS).

Critical challenges identified in the utilization focus area include the cost-effective use of CO₂ as a feedstock for chemical synthesis, or its integration into pre-existing products. The efficiency (reaction conversion and the amount of CO₂ sequestered in a product) and energy use (the amount of energy required to utilize CO₂ in existing products) of these utilization processes also represent a critical challenge.

In order to meet these challenges, metrics are developed to enable comparison of such technologies and utilization processes. In the not-too-distant past, authors and organizations have described using “sustainability metrics” to guide decision-making in the process industries for the goals of environmental protection, economic prosperity, and social benefit. [2, 3, 4, 5]

2 Introduction

A *metric*, in the context we are using here, is defined as “a standard of measurement.” [6]

Various aspects of research and development (R&D) projects, also thought of as processes or technologies, can have standards of measurement developed and defined for them; the methodology for doing so is the objective of this report.

The two most common groups of metrics are those dealing with economics (costs and values of inputs, outputs, and processes, including capital and operating costs) and performance (mass conversion, energy efficiency, and, generally speaking, energy and mass balance derived parameters).

Economic and performance metrics are needed to be able to compare and/or screen varied R&D projects and technologies from different perspectives or points of view. It is important to have available as wide a set of metrics as possible, because, at this stage of development, there are usually gaps in the information available; these vary from project to project and technology to technology, such that not every metric can be evaluated for each. Having a diverse set of metrics allows for R&D projects and technologies to be compared by at least one or more of these metric methods, and for meaningful comparisons to be drawn.

Depending on the priorities of an organization or the goals of R&D programs, different metrics may be weighted differently in their application. Thus, some metrics may be considered more important than others.

Such assessments and comparisons assist in decision-making for allocating limited funds and resources to the most promising processes or technologies, according to the metrics which are judged to be the most important.

The metrics developed here are applied to CO₂ utilization for beneficial use. This utilization of CO₂ involves the chemical conversion of the CO₂ into useful and valued products (such as polycarbonate plastics), or integrating the CO₂ into pre-existing products (such as cement or concrete).

3 Developing the Metrics

When developing the metrics for the utilization of CO₂, it is important to understand the essence of the utilization technology or process, as well as to ask the following questions:

- What reactions are involved?
- What are the reactants and co-reactants?
- What are the products and co-products?
- What are the reaction conditions?
- What are the heats of reaction?
- What catalysts and co-catalysts are required?
- Where are the system boundaries drawn?
- Is the system batch, or continuous and steady-state?
- At what scale has the technology or process been demonstrated?

In cases where the new CO₂ utilization technology or process, also referred to as pathway, has a corresponding existing or traditional non-utilization pathway for the product of interest, it is important to understand all the pertinent details of that pathway, because some of the metrics compare the new pathway benefits relative to the traditional one.

It is useful to consider various aspects of each technology or process under each of the categories of economics and performance.

Questions to be asked under economics are as follows:

- What market does the process product target, and what is the size of the market?
- What are the unit and total costs of all the material (feedstocks) and energy inputs at the conditions required by the reaction(s), or at the system boundary?
- What is the availability of all material feedstocks required?

- What are per unit and total costs (or values) of all the material and energy outputs, including any waste streams, as they exit the reaction, or as defined at the system boundary?
- What are the capital costs of all the equipment specified within the system boundary?
- What are operating costs of the process as specified within the system boundary?
- What is the reactor volume required for the scale of the process?
- What is the plot space required for the scale of the process?
- What are the known hazards, and what are the likely safeguards?
- If the new process is replacing an existing process, what are the above parameters for the existing process?

Questions to be asked under performance are as follows:

- What is the conversion efficiency or yield of each reaction at the specified reaction conditions?
- What is the mass and energy balance, including pressures, temperatures, flowrates, compositions, and process flow diagram, for the system as defined above?
- Has the technology or process been demonstrated as a working system, including any recycle streams, heat integration, and intermediate and/or final separation of products to meet specified product purities?
- What is the consumption rate and useful life of any catalysts/co-catalysts?
- What is the intermittent or continuous rate of any purge or waste streams and are these streams hazardous materials?
- If the new process is replacing an existing process, what are the above parameters for the existing process?

4 Methodology

The methodology for 12 metrics that were developed for CO₂ utilization technologies and processes is detailed below. The 12 metrics are grouped under the following five subheadings:

- Performance
- Cost
- Emissions
- Market
- Safety

4.1 Performance Metrics

4.1.1 CO₂ Utilization Efficiency

CO₂ utilization efficiency is defined as the amount of CO₂ utilized (mass basis) per unit amount of CO₂ fed to the utilization process. This represents the simplest way of thinking about a CO₂ utilization metric. It is a dimensionless ratio and is preferably expressed as a percentage. The higher the percentage, the more efficient the CO₂ utilization process.

For a continuous flow process, this metric is expressed as the flow rate of CO₂ into the process minus the flow rate of CO₂ leaving the process divided by the flow rate of CO₂ into the process.

$$\begin{aligned} CO_2 \text{ Utilization Efficiency (\%)} &= \frac{\text{tonnes } CO_2 \text{ utilized}}{\text{tonnes } CO_2 \text{ fed to process}} \times 100 \\ &= \frac{(\text{tonnes/year } CO_2 \text{ in} - \text{tonnes/year } CO_2 \text{ out})}{\text{tonnes/year } CO_2 \text{ in}} \times 100 \quad (1) \end{aligned}$$

4.1.2 CO₂ Utilization Potential

CO₂ utilization potential is the amount of CO₂ that would be utilized (mass basis) to meet the desired product's market demand, relative to the amount of CO₂ emitted from a user-specified reference CO₂ emitter or plant. This metric represents the CO₂ emission stream's potential to be utilized in a marketable product. It is a dimensionless ratio and can be expressed as a percentage. The geographic basis for the product market demand should be specified, e.g., the U.S., North America, or the world. Also, the CO₂ emission stream reference basis should be defined, since the metric is dependent on this reference, e.g., a single power plant emission, total U.S. coal-fired power plants emissions, etc. Furthermore, the reference CO₂ basis can be further defined as the CO₂ emitted, or as the CO₂ captured in a carbon capture scenario. In the latter definition, the CO₂ captured represents the CO₂ available to the utilization process.

$$CO_2 \text{ Utilization Potential (\%)} = \frac{\text{tonnes/year } CO_2 \text{ utilized to meet market demand}}{\text{tonnes/year } CO_2 \text{ available from reference plant}} \times 100 \quad (2)$$

4.1.3 CO₂ Utilization Intensity

CO₂ utilization intensity is the amount of CO₂ utilized (mass basis) per unit amount of the desired product. This metric is a dimensionless ratio and should be expressed as a percentage. It may be thought of as a 'mass version' of the chemical reaction stoichiometry (which is done on a mole basis).

$$CO_2 \text{ Utilization Intensity} = \frac{\text{tonnes } CO_2 \text{ utilized}}{\text{tonnes product produced}} \times 100$$

$$= \frac{(\text{tonnes/year } CO_2 \text{ in} - \text{tonnes/year } CO_2 \text{ out})}{\text{tonnes product produced}} \times 100 \quad (3)$$

4.1.4 CO₂ Integration Reaction Rate

The CO₂ integration reaction rate is the molar rate of CO₂ utilized per unit of reactor volume. The molar rate can be on any time basis, such as lb-mol/hr, and the reactor volume can be on any convenient volume basis, such as gallons. In this case, the metric units would be lb-mol/(gal·hr). This metric is a measure of the reactor volume required in the technology's current state of development to meet the desired production rate.

$$CO_2 \text{ Integration Reaction Rate (lb-mol/gal} \cdot \text{hr)} = \frac{\text{lb-mol/hr } CO_2 \text{ utilized}}{\text{gallons of reactor volume required for reaction}} \quad (4)$$

4.1.5 CO₂ Energy Utilization

The CO₂ energy utilization metric is defined as the net amount of energy required per unit amount of CO₂ utilized (mass basis). It is a measure of the energy efficiency of the technology or process to utilize CO₂. The units for the energy utilization metric are kW/(tonne CO₂ per hour).

$$CO_2 \text{ Energy Utilization (kW/(tonne } CO_2 \text{/hr))} = \frac{\text{kW energy required}}{\text{tonnes/hour } CO_2 \text{ utilized}} \quad (5)$$

4.2 Cost Metrics

4.2.1 Product Marketability

The product marketability metric is the cost to make a unit amount of the desired product relative to the market value of that product. This metric is a dimensionless ratio and should be expressed as a percentage.

$$\text{Product Marketability (\%)} = \frac{\$ \text{ cost to make a tonne of desired product}}{\$ \text{ per tonne market value of desired product}} \times 100 \quad (6)$$

4.2.2 Incremental Cost Reduction

If there is a traditional process for making the desired product that the new CO₂ utilization process is replacing, then the incremental cost reduction metric is the incremental reduction in cost by the new utilization process over the traditional process. The units of this metric are \$ per tonne of product. This metric needs to have a positive value to show there is a cost saving to be had in replacing the traditional process.

$$\text{Incremental Cost Reduction (\$/tonne)} = \frac{(\$ \text{ cost to make a tonne of product by traditional process}) - (\$ \text{ cost to make a tonne of product by new process})}{1} \quad (7)$$

4.2.3 Cost per Tonne CO₂ Utilized

The cost per tonne of CO₂ utilized metric is the sum of annualized capital and operating costs of the utilization process relative to the tonnes of CO₂ utilized. The costs of the process are to include infrastructure, raw materials, processing, byproduct disposal, and utilities costs, as well as any other costs. The units of this metric are \$ per tonne of CO₂. This metric is dependent on the maturity or stage of development of the technology or process, and whether the costs are known or can be reasonably estimated.

$$\text{Cost per Tonne CO}_2 \text{ Utilized (\$/tonne)} = \frac{\sum [\text{annualized capital and operating costs, } \$/\text{year}]}{\text{tonnes/year CO}_2 \text{ utilized}} \quad (8)$$

4.3 Emissions Metrics

4.3.1 CO₂ Emissions Reduction

If there is a traditional process for making the desired product that the new CO₂ utilization process is replacing, then the CO₂ emissions reduction metric is the amount of CO₂ emissions reduction per unit amount of product in the new process, relative to that in the traditional process. This metric is a dimensionless ratio and should be expressed as a percentage. The greater the value, the greater is the CO₂ emissions reduction.

$$\text{CO}_2 \text{ Emission Reduction (\%)} = \frac{\text{tonnes/year CO}_2 \text{ emitted in existing process} - \text{tonnes/year CO}_2 \text{ emitted in new process}}{\text{tonnes/year CO}_2 \text{ emitted in existing process}} \times 100 \quad (9)$$

4.3.2 CO₂ Avoided Potential

If there is a traditional process for making the desired product that the new CO₂ utilization process is replacing, then the CO₂ avoided potential metric is the amount of CO₂ avoided by the new process over the traditional process, and assumed to offset CO₂ emissions from a user-specified reference CO₂ emitter or plant. This metric is a dimensionless ratio and should be expressed as a percentage. Put another way, the CO₂ avoided potential is the percentage of the reference plant CO₂ emissions that the new process would avoid producing, when considering the utilization process and reference CO₂ emitter within the same envelope.

$$\begin{aligned}
 CO_2 \text{ Avoided Potential (\%)} &= \frac{\text{tonnes/year of } CO_2 \text{ avoided to meet market demand}}{\text{tonnes/year of } CO_2 \text{ emitted from reference plant}} \times 100 \\
 &= \frac{\text{tonnes/year } CO_2 \text{ emitted from existing process} - \text{tonnes/year } CO_2 \text{ emitted from new process}}{\text{tonnes/year of } CO_2 \text{ emitted from reference plant}} \times 100 \quad (10)
 \end{aligned}$$

4.4 Market Metric

4.4.1 Product Supply-Demand

The product supply-demand metric is the percentage of the desired product market that can be satisfied with the new process or technology, taking into consideration feedstock or catalyst availability, or other limitations. This metric is a dimensionless ratio that should be expressed as a percentage. The geographic basis for the product market demand should be specified, e.g., the U.S., North America, or the world.

$$\text{Product Supply-Demand Metric (\%)} = \frac{\text{tonnes/year of product that can be produced}}{\text{tonnes/year of market demand for that product}} \times 100 \quad (11)$$

4.5 Safety Metric

4.5.1 Relative Safety and Environmental Benefits

The relative safety and environmental benefits metric is a composite assessment of the raw materials and processing conditions, including any environmental benefits, of the new process relative to those of any existing process for the same product. The metric assessment is either improved, no change, or reduced.

The relative safety ranking uses the National Fire Protection Association (NFPA) Standard 704 “fire diamond” category hazard values, which range from 0 to 4, with 0 meaning no hazard and 4 meaning severe hazard. [7] The NFPA categories are those of health, flammability, and instability/reactivity. There is also a special notice category for oxidizing materials, materials having unusual reactivity with water, and simple asphyxiants. [8]

An improved relative safety assessment could be based on reduced reactor temperature and/or pressure, elimination of a hazardous feedstock or catalyst, etc.

Examples of improved environmental benefits assessments include the elimination of a petroleum-based feedstock, elimination of a toxic by-product, reduction in raw water consumption, or reduction in air pollutant emissions.

5 Conclusions

The metrics presented in this report were developed for use with CO₂ utilization through chemical conversion processes. Other types of metrics could be developed as desired, such as those used for chemistry: yield, atom economy, and reaction mass efficiency. [4]

These metrics give simple standards of measurement to gauge performance and economics of R&D projects relative to their contemporary counterparts, and between interdisciplinary utilization fields. This in itself provides useful tools for decision-makers for benchmarking performance, tracking improvement, evaluating products and processes, and developing strategies for prioritizing and allocating limited resources, such as R&D funding. [3]

6 References

1. **National Energy Technology Laboratory (NETL).** Carbon Storage: CO₂ Utilization Focus Area. [Online] 2013.
http://www.netl.doe.gov/technologies/carbon_seq/corerd/co2utilization.html.
2. **Institution of Chemical Engineers.** THE SUSTAINABILITY METRICS: Sustainable Development Progress Metrics – Recommended for use in the Process Industries. [Online] 2002.
http://www.icheme.org/communities/subject_groups/sustainability/resources/~//media/Documents/Subject%20Groups/Sustainability/Newsletters/Sustainability%20Metrics.ashx.
3. **Schwarz, J., Beloff, B., Beaver, E.** Use Sustainability Metrics to Guide Decision-Making. *CEP Magazine*. [Online] 2002. <https://www.aiche.org/resources/publications/cep/2002/july/use-sustainability-metrics-guide-decision-making>.
4. **Constable, D.J.C., Curzons, A.D., Cunningham, V.L.** Metrics to 'green' chemistry - which are the best? *Green Chemistry*. [Online]
http://www.researchgate.net/publication/228852772_Metrics_to_'green'_chemistry-which_are_the_best/file/79e4150ba466dd3743.pdf.
5. **U.S. EPA.** AIChE Journal. *Sustainable Development and Sustainability Metrics*. [Online]
<http://library.certh.gr/libfiles/PDF/GEN-PAPYR-518-SUSTAINABLE-by-SIKDAR-in-AICHEJ-V-49-ISS-8-PP-1928-1932-Y-2003.pdf>.
6. **Merriam-Webster.** [Online] 2013. <http://www.merriam-webster.com/dictionary/metric>.
7. **The University of Oregon, Chemistry Teaching Laboratories.** NFPA 704 Hazard Identification System. [Online] 2006. <http://chemlabs.uoregon.edu/Safety/NFPA.html>.
8. **National Fire Protection Association.** [Online] 2013. <http://www.nfpa.org/codes-and-standards/document-information-pages?mode=code&code=704>.